Some Software Packages for Partial SVD Computation

Zhouchen Lin

Abstract—This technical report introduces some software packages for partial SVD computation, including optimized PROPACK, modified PROPACK for computing singular values above a threshold and the corresponding singular vectors, and block Lanczos with warm start (BLWS). The current version is preliminary. The details will be enriched soon.

Index Terms—Partial SVD, PROPACK, Lanczos Method

arXiv:1108.1548v2 [math.OC] 9 Aug 2011

1 Introduction

This technical report introduces some software packages for partial SVD computation, including optimized PROPACK, modified PROPACK for computing singular values above a threshold and the corresponding singular vectors, and block Lanczos with warm start (BLWS). The current version is preliminary. The details will be enriched soon.

2 Optimized PROPACK

PROPACK [3] is nowadays widely used in solving nuclear norm minimization problems in order to compute the partial SVD. We optimized PROPACK and obtained 15% to 20% speed up. The optimization is mainly by rewriting the Gram-Schmidt orthogonalization in the Lanczos procedure. The code is downloadable at http://research.microsoft.com/~zhoulin/optPROPACK.zip

3 Modified PROPACK

The current PROPACK [3] can only output given *number* of principal singular values and vectors. However, when solving nuclear norm minimization problems, we are often faced with singular value thresholding [1], which requires the principal singular values that are greater than a given *threshold*. So we modified PROPACK to provide this functionality. The pseudo code is as in Algorithm 1 [2].

The code is downloadable at http://research.microsoft.com/~zhoulin/ThresholdLANSVD.zip

Algorithm 1 Partial SVD by a Threshold

Input: Matrix A, threshold $svthr$, initial vector p_0, size K of the bidiagonal matrix B, $\beta_1 = \|p_0\|$, $u_1 = p_0/\beta_1$, $i = 1$, $minsv = svthr + 1$,
while $minsv \geq svthr$ **do**
 while $i \leq K$ **do**
 $r_i = A^T u_i - \beta_i v_{i-1}$, $r_i = \text{reorth}(r_i)$,
 $\alpha_i = \|r_i\|$, $v_i = r_i/\alpha_i$,
 $p_i = Av_i - \alpha_i u_i$, $p_i = \text{reorth}(p_i)$,
 $i \leftarrow i + 1$.
 end while
 Compute the SVD of the bidiagonal matrix B to obtain the singular values, stored in a vector s.
 $neig =$ the number of accurate singular values.
 $minsv =$ the minimum of those accurate singular values.
 Update K by

$$K = \begin{cases} \min(K + 100, \max(2 + K, \\ \ \text{length}(s > svthr) * K/neig)), & \text{if } neig > 0, \\ 2 * K, & \text{otherwise.} \end{cases}$$

end while

4 Block Lanczos with Warm Start (BLWS)

When solving nuclear norm minimization problems, we have to solve the partial SVD multiple times. However, the matrix to compute the partial SVD only changes slightly over iteration. To utilize this fact, we propose using the block Lanczos with warm start technique to cut the computation in each iteration [5]. The code is downloadable at http://research.microsoft.com/~zhoulin/BLWS.zip

The code includes the BLWS technique for eigenvalue decomposition (BL_EVD.m) and that for singular value decomposition (BL_SVD.m), and also an exemplary usage of BL_SVD in solving the RPCA problem [4].

• *Z. Lin is with Microsoft Research Asia, Beijing, China, 100080. E-mail: zhoulin@microsoft.com.*

References

[1] J. Cai, E. Candès, and Z. Shen. A singular value thresholding algorithm for matrix completion. *preprint, code available at http://svt.caltech.edu/code.html*, Sep 2008.

[2] M. Chen. Algorithms and implementations of matrix reconstruction (in chinese). Master Thesis, available at http://research.microsoft.com/∼zhoulin/Publications/2010-MatrixReconstruction.pdf, 2010.
[3] R. M. Larsen. Lanczos bidiagonalization with partial reorthogonalization. Department of Computer Science, Aarhus University, Technical report, DAIMI PB-357, code available at http://soi.stanford.edu/∼rmunk/PROPACK/, Sep 1998.
[4] Z. Lin, M. Chen, and Y. Ma. The augmented lagrange multiplier method for exact recovery of corrupted low-rank matrix. Technical Report UILU-ENG-09-2215, UIUC, October 2009 (arXiv: 1009.5055)., 2009.
[5] Z. Lin and S. Wei. A block Lanczos with warm start technique for accelerating nuclear norm minimization algorithms. *Optimization Letters*, submitted, arxiv:1012.0365.